

## PRODUCT DESCRIPTION



- The high-performance of attenuation allows coaxial cable to be used in different RF systems.
- Wide range of applications, such as indoor distribution, broadcast, various base stations, wireless cellular, and others.
- Lower VSWR, perfect shielding effectiveness, and extraordinary inter-modulation performance lead to fewer energy loss and outer interference.

## CONSTRUCTION

Inner conductor	Copper Clad Aluminum	Φ 4.80±0.05mm
Insulation	Physically foamed PE	Φ 12.20±0.20mm
Outer conductor	Ring corrugated copper	Φ 13.70±0.20mm
Jacket	Black PE	Φ 15.40±0.20mm

## MECHANICAL PROPERTIES

Min. single bending radius	mm	70
Min. repeated bending radius(5 times)	mm	125
Min. tensile strength	N	1130
Recommended maximum clamp spacing	m	1

## ELECTRICAL PROPERTIES

Impedance	Ω	50±3
Nominal capacitance	pF/m	76
Nominal inductance	μH/m	0.19
Nominal Propagation velocity	%	86
DC breakdown voltage	kV	4.0
Insulation resistance	MΩ•km	>5000
Peak power rating	kW	40
Cut-off frequency	GHz	8.8

## TRANSMISSION PROPERTIES

Frequency MHz	Attenuation @20°C, dB/100m(dB/100ft)	Power @40°C, kW
100	2.17(0.66)	3.49
450	4.75(1.45)	1.59
690	5.97(1.82)	1.34
800	6.46(1.97)	1.17
900	6.85(2.09)	1.10
1000	7.28(2.22)	1.04
1800	10.10(3.08)	0.75
2000	10.70(3.26)	0.71
2200	11.24(3.43)	0.65
2400	11.78(3.59)	0.62
2500	12.06(3.68)	0.61
2600	12.34(3.76)	0.60
2700	12.61(3.84)	0.59
3000	13.40(4.09)	0.57

Attenuation values may be with a tolerance of 5%.

## VSWR

700-800MHz	≤	1.13
800-1000MHz	≤	1.15
1700-2200MHz	≤	1.15
2400-2700MHz	≤	1.15

## ENVIRONMENTAL PROPERTIES

Recommended storage temperature	°C	-55~+85
Recommended installation temperature	°C	-40~+60
Recommended operating temperature	°C	-55~+85
2011/65/EU(ROHS)		compliant

### Your dealer:



**Advantec Srl**  
 Via Caduti per la Libertà, 13  
 10060 Pinasca TO - Italy  
 Tel. +39 0121326770  
 info@advantec.it - www.advantec.it